

# Gas Ranges with Griddle Tops

## Standard Features

- Stainless steel exterior including front, back sides, kick plate, back guard and over shelf
- Heavy duty 3/4" thick polished steel griddle plate
- Drip tray provided under burners to catch grease drippings
- 27,000 BTU griddles & 27,000 BTU oven burners
- Oven temperature range between 175°F to 550°F
- Standing pilot for open top burners
- Oven pilot with 100% safety shut off
- Enamel interior oven for easy cleaning
- Multiple position oven rack guides
- One (1) chrome oven rack per oven standard
- Available in Natural and Propane
- 3/4" NPT rear gas connection and regulator provided

## MODELS:

ATO-24G/ATO-36G

ATO-24G



ATO-36G



1 YR WARRANTY ON ALL PARTS AND LABOR (US ONLY)



Conforms to ANSI  
STD Z83.11-2009 (2011)  
Certified for CSA  
STD 1.4B-2009 (2011)  
Conforms to NSF/ANSI STD.4



**SPECIFICATIONS**

| Model   | Gas type | Burner name | BTU's  | Number of burners | Oven size (inch)         | Griddle working area (inch) | Valve types | Net weight (lbs) | Gross weight (lbs) |
|---------|----------|-------------|--------|-------------------|--------------------------|-----------------------------|-------------|------------------|--------------------|
| ATO-24G | NG       | Griddle     | 48,000 | 2                 | 20x26x14                 | 24x20 <sup>5/8</sup>        | Pilot light | 367              | 468.5              |
|         |          | Oven        | 24,000 | 1                 |                          |                             |             |                  |                    |
|         | LP       | Griddle     | 48,000 | 2                 |                          |                             |             |                  |                    |
|         |          | Oven        | 24,000 | 1                 |                          |                             |             |                  |                    |
| ATO-36G | NG       | Griddle     | 75,000 | 3                 | 26 <sup>1/2</sup> x26x14 | 36x20 <sup>5/8</sup>        | Pilot light | 494              | 621.7              |
|         |          | Oven        | 27,000 | 1                 |                          |                             |             |                  |                    |
|         | LP       | Griddle     | 75,000 | 3                 |                          |                             |             |                  |                    |
|         |          | Oven        | 27,000 | 1                 |                          |                             |             |                  |                    |

**PLAN VIEW**

