

# 60" Combination Gas Ranges

## Standard Features

- Stainless steel exterior including front, back sides, kick plate, back guard and over shelf
- 60" combination ranges standard with either a 24", 36" or 48" griddle top with 2, 4 or 6 burners
- Heavy duty 3/4" thick polished steel griddle plate
- Drip tray provided under burners to catch grease drippings
- 25,000 BTU top burners, 27,000 BTU griddle & 27,000 BTU oven burners
- Oven temperature range between 175°F to 550°F
- Standing pilot for open top burners
- Oven pilot with 100% safety shut off
- Enamel interior oven for easy cleaning
- Multiple position oven rack guides
- One (1) chrome oven rack per oven standard
- Available in Natural and Propane
- 3/4" NPT rear gas connection and regulator provided

## MODELS:

ATO-2B48G/ATO-4B36G/ATO-6B24G

**ATO-2B48G**



**ATO-4B36G**



**ATO-6B24G**



1 YR WARRANTY ON ALL PARTS AND LABOR (US ONLY)



Conforms to ANSI  
STD Z83.11-2009 (2011)  
Certified for CSA  
STD 1.8B-2009 (2011)  
Conforms to NSF/ANSI STD.4



**SPECIFICATIONS**

Model	Gas type	Burner name	BTU's	Number of burners	Oven size (inch)	Hot plates working area (inch)	Griddle working area (inch)	Valve types	Net weight (lbs)	Gross weight (lbs)
ATO-2B48G	NG	Hot plates	50,000	2	26 <sup>1/2</sup> ×26×14	2pcs 11 <sup>4/5</sup> ×11 <sup>4/5</sup>	48×20 <sup>5/8</sup>	Pilot light	805	970.5
		Griddle	102,000	4						
		Oven	54,000	2						
	LP	Hot plates	46,000	2						
		Griddle	102,000	4						
		Oven	54,000	2						
ATO-4B36G	NG	Hot plates	100,000	4	26 <sup>1/2</sup> ×26×14	4pcs 11 <sup>4/5</sup> ×11 <sup>4/5</sup>	36×20 <sup>5/8</sup>	Pilot light	792	948.9
		Griddle	75,000	3						
		Oven	54,000	2						
	LP	Hot plates	92,000	4						
		Griddle	75,000	3						
		Oven	54,000	2						
ATO-6B24G	NG	Hot plates	150,000	6	26 <sup>1/2</sup> ×26×14	6pcs 11 <sup>4/5</sup> ×11 <sup>4/5</sup>	24×20 <sup>5/8</sup>	Pilot light	775	940.5
		Griddle	48,000	2						
		Oven	54,000	2						
	LP	Hot plates	138,000	6						
		Griddle	48,000	2						
		Oven	54,000	2						

**PLAN VIEW**

