

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

REMOTE BLAST CHILLER

BF201DP Solid Door Roll-In Blast Chiller

MODEL: BF201DP-1P



Note: Shown With Optional Ramp

5 Year Parts/Labor Warranty Available **5 Year Compressor Warranty**

CABINET CONSTRUCTION

- Stainless steel exterior and interior
- Die-formed interior floor has rounded corners
- Central drain for easy cleaning
- Anti-condensation perimeter heating around door opening
- Ergonomic door handle and stainless steel
- Snap in place magnetic gaskets self closing door with hold open stop at 100°
- Soft and hard, timed or core probe blast chilling
- Soft and hard, timed or core probe shock freezing
- Automatic recognition of core probe
- Multi point sensor temperature display button
- Core probe heater button
- HACCP alarm display button
- · Pre-cooling cycle button
- Adjustable evaporator fan speed button
- Timed manual defrost button
- USB data recorder
- Infinity mode program with adjustable set point
- Automatic conservation mode at end of cycle
- On board recipe book with 68 pre-set programs
- 99 Free memory positions for custom programs
- LCD illuminated temperature display
- Real time clock
- One, high precision heated multi sensor probe
- Maximum interior dimensions for carts: 26"W x 33"D x 75"H (not included)
- Ramp dimension: 35.3"W x 31.9"D (ramp not included)

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- UV sterilization lamp (must be added at time of order)
- Single sensor probes (up to 4 possible)
- Change door swing
- · Ramp (not included)

REFRIGERATION SYSTEM

- Remote refrigeration system uses R404 refrigerant (condensing unit to be provided by others)
- Evaporator fitted with a high flow rate fan insures maximum cooling efficiency
- Indirect air flow assures highest product quality
- Manual defrosting with door open on a timed cycle
- Blast chilling (194°F to 37°F in 90 minutes) or shock freezing (194°F to 0°F in 240 minutes) cycles









3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	BF201DP-1P
EXTERNAL DIMENSIONAL DATA	
Width Overall (in)	47.24"
Depth Overall (in)	46.26"
Height Overall (in)	87.80"
Number of Doors	1
Width, Door Opening (in)	74.02"
Door Opening (in)	27.56" x 75.59"
PERFORMANCE DATA	
Sheet Pan Capacity* (18" x 26")	20
Steam Table Pan Capacity* (12" x 20")	20
Chilling Capacity In 90 Min	175 lbs
Freezing Capacity In 240 Min	115 lbs
Climate Class	5
Capacity Mobile Cart(s)	1 GN 1/1
ELECTRICAL DATA	
Cabinet Voltage	208-240/60/1
Total Amperes	2.5
NEMA Plug	N.A.
REFRIGERATION DATA	
Condensing Unit Size, HP	N.A.
Refrigerant	R404
Capacity (BTU/Hr) (113°F/-13°F)	21,598
Heat Rejection (W) (14°F/95°F)	N.A.
Refrigerant Amount (lbs)	N.A.
WEIGHT DATA	
Gross Weight - Crated	962 lbs
Height - Crated	91"
Width - Crated	50"
Depth - Crated	70"

^{*}Note - Pans not included

Remote Blast Chiller/Shock Roll-In Freezer Model: BF201DP-1P







