



BEVERAGE-AIR®

Project: _____	AIA#
Item: _____	
Location: _____	SIS#
Approved: _____	

REMOTE BLAST CHILLER

BF202AP Solid Door Roll-Thru Blast Chiller

MODEL:
BF202AP-2P

BF202AP BLAST CHILLER/SHOCK ROLL-THRU FREEZER

5 Year Parts/Labor Warranty Available

5 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel exterior and interior
- Die-formed interior floor has rounded corners
- Central drain for easy cleaning
- Anti-condensation perimeter heating around door openings
- Ergonomic door handles and stainless steel
- Snap in place magnetic gaskets self closing doors with hold open stop at 100°
- Soft and hard, timed or core probe blast chilling
- Soft and hard, timed or core probe shock freezing
- Automatic recognition of core probe
- Multi point sensor temperature display button
- Core probe heater button
- HACCP alarm display button
- Pre-cooling cycle button
- Adjustable evaporator fan speed button
- Timed manual defrost button
- USB data recorder
- Infinity mode program with adjustable set point
- Automatic conservation mode at end of cycle
- On board recipe book with 68 pre-set programs
- 99 Free memory positions for custom programs
- LCD illuminated temperature display
- Real time clock
- One, high precision heated multi sensor probe
- Maximum interior dimensions for carts: 30"W x 44"D x 75"H (not included)
- Ramp dimensions: 39.2"W x 31.9"D (ramps not included)



Note: Shown With Optional Ramps

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- UV sterilization lamp (must be added at time of order)
- Single sensor probes (up to 4 possible)
- Change door swing
- Ramps (not included)

REFRIGERATION SYSTEM

- Remote refrigeration system uses R404 refrigerant (condensing unit to be provided by others)
- Evaporator fitted with a high flow rate fan insures maximum cooling efficiency
- Indirect air flow assures highest product quality
- Manual defrosting with door open on a timed cycle
- Blast chilling (194°F to 37°F in 90 minutes) or shock freezing (194°F to 0°F in 240 minutes) cycles



Please verify qualifying units by visiting:
www.energystar.gov/cfs

3779 Champion Blvd., Winston-Salem, NC 27105
1-888-845-9800 Fax: 1-336-245-6453
Beverage-Air.com Sales@bevair.com




BEVERAGE-AIR®

MODEL		BF202AP-2P
EXTERNAL DIMENSIONAL DATA		
Width Overall (in)		59.06"
Depth Overall (in)		59.65"
Height Overall (in)		87.80"
Number of Doors		2
Width, Door Openings (in)		124.41"
Door Openings (in)		31.5" x 75.59"
PERFORMANCE DATA		
Sheet Pan Capacity* (18" x 26")		20
Steam Table Pan Capacity* (12" x 20")		40
Chilling Capacity In 90 Min		465 lbs
Freezing Capacity In 240 Min		310 lbs
Climate Class		5
Capacity Mobile Cart(s)		2 GN 2/1
ELECTRICAL DATA		
Cabinet Voltage		208-240/60/3
Total Amperes		9.0
NEMA Plug		N.A.
REFRIGERATION DATA		
Condensing Unit Size, HP		N.A.
Refrigerant		R404
Capacity (BTU/Hr) (113°F/-13°F)		46,736
Heat Rejection (W) (14°F/95°F)		N.A.
Refrigerant Amount (lbs)		N.A.
WEIGHT DATA		
Gross Weight - Crated		1054 lbs
Height - Crated		90"
Width - Crated		56"
Depth - Crated		71"


*Note - Pans not included

Remote Blast Chiller/Shock Roll-Thru Freezer Model: BF202AP-2P


Model Views



PLAN VIEW



ELEVATION VIEW



SIDE VIEW

