

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

# P SERIES TOP MOUNT FREEZER

PF1HC Solid Door Reach-In Hydrocarbon Series

MODEL: PF1HC-1AS



5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

### **CABINET CONSTRUCTION**

- Exterior stainless steel front and side (galvanized top, bottom & back)
- · Interior is made of corrosion resistant aluminum
- · Stainless steel door liner
- · Full electronic control
- · Expansion valve technology
- Self-closing door with 120° stay-open feature
- · 22 Gauge stainless steel door
- · LED interior light
- Cylinder lock
- · Snap-in magnetic gaskets for positive door seal
- · Hinged front shroud
- Energy saving thermal breaker
- · Stainless steel breaker caps
- Three (3) heavy-duty epoxy wire coated shelves
- 6" High adjustable stainless steel legs
- 8' Cord and plug (see electrical data for details)

### **OPTIONS & ACCESSORIES**

- 3 Year parts/labor standard, additional 2 year warranty available
- Stainless steel case back
- Stainless steel interior
- Additional shelves
- 3" or 6" casters
- 6" Seismic legs
- Tray slides (type A & A/C)
- Door swing orientation (at time of order)
- Remote option\* (see note back on page)

### **REFRIGERATION SYSTEM**

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- · Adaptive defrost
- Epoxy coated evaporator coil, located out of the food zone
- Freezer capable of maintaining product temperature down to -10°F






3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	PF1HC-1AS
EXTERNAL DIMENSIONAL DATA	
Width Overall	26 ½"
Depth Overall with Handle	34 ¾"
Height Overall	84 1⁄8"
Number of Doors	1
Depth with Door Open 90°	56 ¾"
Door Opening (in)	21 ½" x 54 ¾"
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.)	21.01
Internal Width Overall (in)	22 ½"
Internal Depth Overall (in)	26"
Internal Height Overall (in)	56 %"
No. of Shelves	3
ELECTRICAL DATA	
Full Load Amperes 115/60/1**	9.1
REFRIGERATION DATA	
Horsepower	3/4
Capacity (BTU/Hr)	2450
Heat Rejection (BTU/Hr)	3675
Charge (lbs/grams/ounces)	0.2866 / 130 / 4.59
SHIPPING DATA	
Gross Weight (crated lbs)	330 lbs
Height - Crated	87"
Width - Crated	45"
Depth - Crated	35"

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

#### **P Series Top Mount Freezer** Model: PF1HC-1AS



## **ELECTRICAL CONNECTION**



115/60/1\*\* Unit pre-wired at factory NEMA 5-15P and include 8' long cord and plug set.

\*\* NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.









