

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

P SERIES TOP MOUNT FREEZER

PF3HC Half-Glass Door Reach-In **Hydrocarbon Series**

MODEL: PF3HC-1BHG



5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel front and side exterior (galvanized rear, back & bottom)
- · Interior is made of corrosion resistant aluminum
- · Full electronic control
- Expansion valve technology
- · Variable speed compressor technology
- Self-closing doors with 120° stay-open feature
- · Glass half doors
- · LED interior light
- · Cylinder locks
- · Snap-in magnetic gaskets for positive door seal
- · Low profile vertical door handles
- · Hinged front shroud
- · Energy saving thermal breaker
- · Stainless steel breaker caps
- Nine (9) heavy-duty epoxy wire coated shelves
- · 6" High adjustable stainless steel legs
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- · Stainless steel case back
- Stainless steel interior
- · Additional shelves
- 3" or 6" Casters
- 6" Seismic legs
- Tray slides (type A & A/C)
- Door swing orientation (at time of order)
- Remote option* (see note back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- Adaptive defrost
- Epoxy coated evaporator coil, located out of the food zone
- Freezer capable of maintaining product temperature down to -10°F








3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	PF3HC-1BHG
EXTERNAL DIMENSIONAL DATA	
Width Overall	77 ¾"
Depth Overall with Handles	33 %"
Height Overall	84 ½"
Number of Doors	6
Depth with Door Open 90°	57 ¾"
Door Openings (in)	21 ½" x 25 ¼"
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.)	68.34
Internal Width Overall (in)	73 ¾"
Internal Depth Overall (in)	26"
Internal Height Overall (in)	56 %"
No. of Shelves	9
ELECTRICAL DATA	
Full Load Amperes 115/60/1	13.9
REFRIGERATION DATA	
Horsepower	(2) 3/4
Capacity (BTU/Hr)	4900
Heat Rejection (BTU/Hr)	7350
Charge (lbs/grams/ounces)	0.2866 / 130 / 4.6
SHIPPING DATA	
Gross Weight (crated lbs)	792 lbs
Height - Crated	88"
Width - Crated	87"
Depth - Crated	45"

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

P Series Top Mount Freezer Model: PF3HC-1BHG



ELECTRICAL CONNECTION



115/60/1** Unit pre-wired at factory NEMA 5-15P and include 8' long cord and plug set.

** NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.









